



New Launch- GOETZE LINER KIT

In continuation to our new launch, we are delighted to introduce piston , ring and Liner assembly :

Application for TATA ACE DIESEL

GOETZE PART NO. : 04333SPL

Cyl. Bore Dia. – 75.0 mm,

No of cylinder - 2



Kit Contents	Existing Part Number
Piston pin and circlip	04333PPC (Moly Coated)
Ring	5764EUROSTEEL
Liner	09920LIN

TECHNICAL DATA PISTONS

Nominal Bore Diameter	75.00 mm
Piston Diameter	74.945 mm
Top Land	12.0 mm
Piston Liner Clearance	0.055mm
Compression Height	42.95 mm
Total Height	69.0 mm
Pin Diameter x Length	23.00 mm x58 mm

TECHNICAL DATA PISTON RINGS

Parameter	TOP	Mid	Oil
Dia	75.00		
Axial	2.0	2.0	3.0
Coating	Nitrided	-	Nitrided
Closed Gap	0.15-0.30	0.15-0.30	0.15-0.30
Material	STEEL	IKA	STEEL
Ring type	BARREL	TAPER FACE	Narrow Land
No. of slots	-	-	28

This product bulletin is an exclusive update of product information from Federal-Mogul . For any query or copy of bulletin , kindly contact technical service section at 0124-478 6104, E Mail- ashish.seth@fmmotorparts.com

THE BEST BRANDS IN THE BUSINESS





New Launch- GOETZE LINER KIT

In continuation to our new launch, we are delighted to introduce piston Ring and Liner assembly :

Application for TATA ACE DIESEL

GOETZE PART NO. : 04333SPL

Special Features Their Advantages

S.No	SPECIAL FEATURES	BENEFITS TO CUSTOMER
1.	SPECIALHIGH STRENGTH ALLOY	Provides optimum strength to piston and Lesser expansion
2.	MOLY COATED SKIRT	Provides wear and scuff resistance.
3.	THIN WALL CROSS SECTION	Lesser expansion hence piston can work at lesser clearance.
4.	LIGHT WEIGHT DESIGN	Lesser fuel consumption
5.	THIN TOP LAND	Helps in reducing emissions
6.	PHOSPHATED	For faster bedding in and initial protection
7.	TOP RING STEEL NITRIDED	Provides wear and scuff resistance
8.	OIL RING STEEL NITRIDED	Provides wear and scuff resistance
9.	NARROW LAND OIL RING	Lesser Lube oil consumption
10.	LOW GAP END RINGS	Low end gap rings specially made for mechanics preference
11.	SUPERIOR LINER	Better durability
12.	SEMI FINISH LINER	To facilitate reboring so as to maintain piston-liner clearance after installation



This product bulletin is an exclusive update of product information from Federal-Mogul . For any query or copy of bulletin , kindly contact technical service section at 0124-478 6104, E Mail- ashish.seth@fmmotorparts.com

THE BEST BRANDS IN THE BUSINESS

