



***New Launch- GOETZE PISTONS***

In continuation to our new launch, we are delighted to introduce piston assembly of:

*Application* HONDA DREAM YUGA/ NEO

*Cyl. Bore Dia. – 50.0 mm*

*Engine set of 1 cylinders*



**GOETZE PART NO. : 01043GMP**

Sizes : STD, 010", 020", 030", 040"



PISTON DATA	Dimensions (mm)
CYL. BORE DIA. (Nominal)	50.0
COMPRESSION. HT.	17.9
TOTAL HT.	36.9
PISTON-LINER CLEARANCE	0.025 (approx.)
PIN OD x ID x LENGTH	12.0/ 8.0x 32.5
Top Ring Groove (width)	0.81
2 <sup>nd</sup> Ring Groove (width)	0.81
Oil Ring Groove (width)	1.51

Some features& benefits:

- As Cast crown and special aluminum alloy for strength
- Thin ring grooves for better sealing of gases & oil scrapping.
- Oil holes in oil ring groove for lower oil consumption.
- Modern design to reduce weight for better mileage

Technical Data, Ring Set No. 2308GTX ("GTX" marking on ring top side)			
Groove	Ring Feature	Ax.Ht. (mm)	End Gap (mm)
1 <sup>st</sup> , Comp.	Steel Gas Nitrided	0.8	0.10-0.30
2 <sup>nd</sup> , Comp.	Taper faced, Phos.	0.8	0.10-0.30
3 <sup>rd</sup> , Oil	3POR, Zin/Tin coated Steel	1.5	0.10-0.70

This product bulletin is an exclusive update of product information from Federal-Mogul . For any query or copy of bulletin , kindly contact technical service section at 0124-478 6104, E Mail- athar.halim@federalmogul.com.

THE BEST BRANDS IN THE BUSINESS

