



New Launch- GOETZE PISTONS & RING PACK

In continuation to our new launch, we are delighted to introduce piston.

For GREAVES GL 435 BS IV

Piston Set no. 01165MP0; Size: STD

Cyl. Bore Dia.– 86 mm

(WITH 2033TKIDCES RING)



Part No:	1165PPC
Application:	G435A IV (CR19:1)
Nominal Bore Diameter :	86.0 mm
Piston Diameter :	86.0 mm
Top Land height:	9 mm
Piston Liner Clearance :	Cold clearance 0.045mm
Compression Height :	44±0.05 mm
Total Height :	72 mm
Pin Diameter x Length	∅20/8x67.7
Pin bore clearance :	0.007mm
Coating	AV-13D Graphite coating
Groove height 1 st / 2 nd and oil	2.09, 2.06 & 3.03mm
Material	CSA18
Coating	AV-13D Graphite coating
OE part number	E10G050005 & E10G050006
Pin hole offset	Nil
Surface treatment	Phosphated
Pin bore feature	St Bore
Matching ring	2033TKIDCES

Some features& benefits:

High Durability Aluminium –Silicon Alloy

Advanced Graphite coating

With Top ring as Semi inlaid ring and narrow land oil ring



This product bulletin is an exclusive update of product information from Federal-Mogul . For any query or copy of bulletin , kindly contact technical service section at [0124-4784543](tel:0124-4784543), E Mail- ashish.seth@fmmotorparts.com.

THE BEST BRANDS IN THE BUSINESS

