






New Launch- GOETZE PISTONS RINGS

In continuation to our new launch, we are delighted to introduce piston rings.



For **ASHOK LEYLAND 401 , 402**
Ring Set no. 6129CKS; Size: STD

Cyl. Bore Dia.– 107.277 mm, 6 Cyl. SET

GROOVE	RING TYPE	SPECIAL FEATURES	BENEFITS
1 ST	 CKS , KV1 Axial Height – 3.2 mm Close Gap – 0.20 .. 0.35	<ul style="list-style-type: none"> - CKS ensures minimal wear & provides excellent scuff resistance. - KV1-high strength material for greater bending break & wear resistance. -barrel Honing provides better sealing with high surface pressure -Low friction due to thin axial height 	<ul style="list-style-type: none"> - Longer Ring life - Longer Ring life - Lesser oil consumption -Lesser oil consumption
2 ND	 Positive Torsion , IKA Axial Height – 2.39 mm Close Gap – 0.25 .. 0.45	<ul style="list-style-type: none"> -IKA MATERIAL - Positive torsion Taper faced scraper for enhanced performance. - Phosphating coating increases oil retention property, reduces bedding in time and provides corrosion resistance 	<ul style="list-style-type: none"> - Lesser oil Consumption - Long ring life - Lesser oil consumption - Better bedding in
3 RD	 Axial Height – 4.77 mm End Gap -0.25 – 0.45mm	<ul style="list-style-type: none"> -Chrome plated profile ground ring -Exerts uniform wall pressure and excellent side sealing. -Effective side sealing due to specially designed expander large oil drainage area 	<ul style="list-style-type: none"> - longer life -Longer Ring life -Lesser oil consumption

Note : Second Compression Rings are marked with “TOP”. Care should be taken to install these rings with “TOP” facing the piston crown.

This product bulletin is an exclusive update of product information from Federal-Mogul . For any query or copy of bulletin , kindly contact technical service section at [0124-4784543](tel:0124-4784543), E Mail- ashish.seth@fmmotorparts.com

THE BEST BRANDS IN THE BUSINESS

