






New Launch- GOETZE RING SET

In continuation to our new launch. we are delighted to introduce piston ring set.



***For FT 60/70 AVL NEW
Ring Set no. 8416SHAKTI; Size: STD
Cyl. Bore Dia.– 111.76 mm, 3 Cyl. Engine***

GROOVE	RING TYPE	SPECIAL FEATURES	BENEFITS
1 ST	 KV1 – Rect. Chrome Inlaid, 1/s bevel Axial Height – 2.385 mm End Gap -0.30-0.50 mm	<ul style="list-style-type: none"> - Chrome Coated Inlaid with phosphating, ensures minimal wear & provides excellent scuff resistance. - KV1-high strength material for greater break & wear resistance. - 1/s bevel at top for positive twist action to reduce blow-by. - Barrel honing provides better sealing with line contact & high surface pressure. 	<ul style="list-style-type: none"> - Longer Ring life - Longer Ring life - More Power - More Power
2 ND	 IKA, Tapper Face, Rev. torsion, Phosphated Axial Height – 2.385 mm End Gap -0.35-0.65 mm	<ul style="list-style-type: none"> -Phosphated for lesser friction & reduces bedding in time. - Reverse Torsion by internally stepped at bottom for lower oil consumption. 	<ul style="list-style-type: none"> - More Power - Lesser Oil Consumption
3 RD	 Chrome coated, Profile Ground oil ring, Spring loaded Axial Height – 3.50 mm End Gap -0.40-0.65 mm	<ul style="list-style-type: none"> - Profile ground contact land for higher radial pressure & better oil scraping effect. - Chrome coated lands provide higher wear resistance & excellent scuff resistance. 	<ul style="list-style-type: none"> - Lesser Oil Consumption - Longer Ring life

Note : Top & Second Compression Rings are marked with “TOP”. Care should be taken to install these rings with “TOP” facing the piston crown.

This product bulletin is an exclusive update of product information from Federal-Mogul . For any query or copy of bulletin , kindly contact technical service section at **0124-4784543**, E Mail- ashish.seth@federalmogul.com.

THE BEST BRANDS IN THE BUSINESS

