






New Launch- GOETZE PISTONS RINGS

In continuation to our new launch, we are delighted to introduce piston rings.



For MAHINDRA ARJUN
Ring Set no. 8205TKFDCES; Size: STD
Cyl. Bore Dia.– 96.0 mm, 1 Cyl. SET

GROOVE	RING TYPE	SPECIAL FEATURES	BENEFITS
1 ST	 Trapeze. Chrome Semi Inlaid Axial Height – 3.0 mm End Gap -0.30-0.45 mm	<ul style="list-style-type: none"> - CKS Coated Semi Inlaid with phosphating, ensures minimal wear & provides excellent scuff resistance. - KV1-high strength material for greater break & wear resistance. - Assymetrical barrel Honed ring for low Lube oil consumption 	<ul style="list-style-type: none"> - Longer Ring life - Longer Ring life - More Power - More Power
2 ND	 F14 Plain Taper faced Axial Height – 2.5 mm End Gap -0.75-1.0 mm	<ul style="list-style-type: none"> - Phosphated for lesser friction & reduces bedding in time. - High Strength material – F14 - Reverse Torsion by internally stepped at bottom for lower oil consumption. 	<ul style="list-style-type: none"> - More Power - Lesser Oil Consumption
3 RD	 Axial Height – 3.0 mm End Gap -0.3 – 0.5 mm	<ul style="list-style-type: none"> - Profile ground contact land for higher radial pressure & better oil scraping effect. - Chrome coated lands provide higher wear resistance & excellent scuff resistance. 	<ul style="list-style-type: none"> - Lesser Oil Consumption - Longer Ring life

Note : Top & Second Compression Rings are marked with “TOP”. Care should be taken to install these rings with “TOP” facing the piston crown.

This product bulletin is an exclusive update of product information from Federal-Mogul . For any query or copy of bulletin , kindly contact technical service section at [0124-4784543](tel:0124-4784543), E Mail- ashish.seth@federalmogul.com.

THE BEST BRANDS IN THE BUSINESS

