



**FEDERAL-MOGUL**  
**MOTORPARTS**



• Engine Bearing



E-CATALOGUE



## Engine Bearing



Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
H1212/7	F/C/R Main Bearing I/Main Bearing	14	STD, 0.25, 0.50, 0.75, 1.00	A/T	3.5 Inches	3.664 Inches	1.60-1.80 Inches	0.080 Inches	
H1212/7	Main Bearing - Leyland	14	STD,0.25,0.50,0.75,1.00	A/T	3.5000 Inches	3.6640 Inches	1.600 Inches	0.080 Inches	ASHOK LEYLAND LEYLAND-370
01-4398/6	Con Rod Bearing-Leyland	12	STD,0.25,0.50,0.75,1.00	A/T	2.3994 Inches	2.5434 Inches	1.370 Inches	0.071 Inches	
H1213/7	F/C/R Main Bearing-Leyland	14	STD,0.25,0.50,0.75,1.00	C/L	3.5000 Inches	3.6640 Inches	1.600 Inches	0.080 Inches	
H1215/7	F/C/R Main Bearing-Leyland	14	STD,0.25,0.50	C/L	3.5000 Inches	3.6640 Inches	1.600 Inches	0.081 Inches	
A250/4	Thrust Washer - Leyland	4	STD, 0.005, 0.010	C/L	3.6380 Inches	4.3980 Inches		0.132 Inches	
71-4398/6	Con Rod Bearing-Leyland	12	STD,0.25,0.50,0.75,1.00	C/L	2.3994 Inches	2.5434 Inches	1.370 Inches	0.071 Inches	
55-4416/6	Con Rod Bush Bearing-Leyland	6	SEMI, 0.010, 0.020	C/L	1.3000 Inches	1.4508 Inches	1.406 Inches		
55-4419/6	Con Rod Bush Bearing-Leyland	6	SEMI, 0.010, 0.020	C/L	1.3000 Inches	1.7790 Inches	1.406 Inches		
N188/2	Cam Shaft Bush-Leyland	2	SEMI	C/L	2.1902 Inches	2.3510 Inches	0.905 Inches		
57-4441/12	Valve Rocker Bush-Leyland	12	STD	C/L	0.8750 Inches	0.9755 Inches	0.900 Inches		
H1214/7	Main Bearing - Leyland	14	STD,0.25,0.50,0.75,1.00	C/L	2.8714 Inches	3.0714 Inches	0.989 Inches	0.098 Inches	ASHOK LEYLAND LEYLAND HINO
57-4617/12	Rocker Lever Arm Bush -Leyland	12	STD	C/L	0.8750 Inches	0.9730 Inches	0.994 Inches		
57-4439/8	Spring Eye Bush - Leyland	8	SEMI	C/L	0.9987 Inches	1.1212 Inches	2.945 Inches		
57-4442	Idler Gear Bush - Leyland	1	SEMI	C/L	1.7488 Inches	2.0008 Inches	1.040 Inches		
57-4618/2	Clutch Withdrawal Sleeve Bush - Leyland	2	SEMI	C/L	1.7488 Inches	0.8750 Inches	0.787 Inches		

Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
57-4443	Differential Trunion Bush -Leyland	1	SEMI	C/L	2.9980 Inches	3.1260 Inches	2.000 Inches		
A251/4	Thrust Washer - Leyland Hino	4	STD, 0.10	C/L	2.9790 Inches	3.2382 Inches		0.980 Inches	ASHOK LEYLAND LEYLAND HINO
71-4399/6	Con Rod Bearing - Leyland	12	STD,0.25,0.50,0.75,1.00	C/L	2.4382 Inches	2.5984 Inches	1.107 Inches	0.079 Inches	ASHOK LEYLAND LEYLAND HINO
01-4399/6	Con Rod Bearing - Leyland	12	STD,0.25,0.50,0.75,1.00	A/T	2.4382 Inches	2.5984 Inches	1.107 Inches	0.079 Inches	ASHOK LEYLAND LEYLAND HINO
55-4417/6	Cod Rod Bush-Leyland	6	SEMI, 0.010, 0.020	C/L	1.3779 Inches	1.5364 Inches	1.516 Inches		ASHOK LEYLAND LEYLAND HINO
55-4418/6	Con Rod Bearing - Leyland	6	SEMI, 0.010, 0.020	C/L	1.3779 Inches	1.5364 Inches	1.516 Inches		ASHOK LEYLAND LEYLAND HINO
57-4619	Oil Pump Drive Shaft Bush-Leyland	1	SEMI	C/L	0.7488 Inches	0.8276 Inches	1.075 Inches		ASHOK LEYLAND LEYLAND HINO
N189/4	Cam Shaft Bush-Leyland	4	SEMI	C/L	2.2042 Inches	2.3656 Inches	1.073 Inches		ASHOK LEYLAND LEYLAND HINO
H1258/5	Main Bearing - Leyland	10	STD	C/L	3.0000 Inches	3.1735 Inches	0.984 inches	0.085 Inches	ASHOK LEYLAND LEYLAND IVECO
71-4624/4	Con Rod Bearing-Leyland	8	STD	C/L	2.2258 Inches	2.3758 Inches	0.975 Inches	0.074 Inches	ASHOK LEYLAND LEYLAND IVECO
57-4621/4	Spindle Pin Bush Rear-Leyland	4	SEMI	C/L	1.4408 Inches	1.5620 Inches	2.010 Inches		ASHOK LEYLAND LEYLAND IVECO
57-4625/2	Steering Knuckle Bush-Leyland	2	SEMI	C/L	1.2508 Inches	1.4072 Inches	1.440 Inches		ASHOK LEYLAND LEYLAND IVECO
57-4626/2	King Pin Bush - Leyland	2	SEMI	C/L	1.6503 Inches	1.7822 Inches	1.573 Inches		ASHOK LEYLAND LEYLAND IVECO
H1275/7	Main Bearing-Tata Cummins	14	STD,0.25,0.50,0.75,1.00	A/T	3.2683 Inches	3.4653 Inches	1.143 Inches	0.097 Inches	TATA TATA-CUMMINS 6BT
71-4573/6	Con Rod Bearing-Tata Cummins	12	STD,0.25,0.50,0.75,1.00	C/L	2.7169 Inches	2.8745 Inches	1.225 Inches	0.077 Inches	TATA TATA-CUMMINS 6BT
55-4706/6	Cod Rod Bush-Tata Cummins	6	SEMI	C/L	1.5620 Inches	1.6968 Inches	1.510 Inches		TATA TATA-CUMMINS 6BT
53-4707	Cam Shaft Bush-Tata Cummins	1	STD	C/L	2.1265 Inches	2.2535 Inches	1.010 Inches		TATA TATA-CUMMINS 6BT
72-4411H	Main Bearing -Tata Motors	2	0.25, 9.50, 0.75	C/L	3.4650 Inches	3.6623 Inches	1.252 Inches		TATA TATA-OM 352
55-4609	Cod Rod-Tata motors	1	SEMI	C/L	1.4980 Inches	1.7488 Inches	1.095 Inches		TATA TATA-OM-352

Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
N187/4	Cam Shaft Bush-Tata Motors	4	SEMI	C/L	2.2032 Inches	2.3634 Inches	1.035 Inches		TATA TATA-OM 352
H1206/7	Main Bearing -Tata Motors	14	STD,0.125,0.25,0.50,0.75,1.00	A/T	3.4650 Inches	3.6623 Inches	0.949 Inches	0.097 Inches	
01-4400/6	Con Rod Bearing - Tata motors	12	STD,0.125,0.25,0.50,0.75,1.00	A/T	2.3628 Inches	2.5598 Inches	1.264 Inches	0.097 Inches	
H1210/7	Main Bearing -Tata Motors	14	STD,0.25,0.50,0.75,1.00	C/L	3.4650 Inches	3.6623 Inches	0.949 Inches	0.097 Inches	
H1207/7	Main Bearing -Tata Motors	14	STD,0.10,0.125,0.25,0.50,0.75,1.00	C/L	3.4650 Inches	3.6623 Inches	0.949 Inches	0.097 Inches	
A252/4	Thrust Washer -Tata Motors	4	STD, 0.005, 0.009	C/L	3.7480 Inches	4.5670 Inches		0.094 Inches	
71-4400/6	Con Rod Bearing - Tata Motors	12	STD,0.125,0.25,0.50,0.75,1.00	C/L	2.3628 Inches	2.5598 Inches	1.264 Inches	0.097 Inches	
55-4597/6	Cod Rod Bush- Tata Motors	6	SEMI, 0.010, 0.020	C/L	1.4173 Inches	1.5364 Inches	1.358 Inches		
55-4598/6	Cod Rod -Tata Motors	6	SEMI, 0.010, 0.020	C/L	1.4173 Inches	1.5364 Inches	1.358 Inches		
55-4420/6	Cod Rod Bush-Tata Motors	6	SEMI, 0.010, 0.020	C/L	1.4173 Inches	1.5364 Inches	1.358 Inches		
55-4414/6	Con Rod Bush-Tata Motors	6	SEMI, 0.010, 0.020	C/L	1.4173 Inches	1.5364 Inches	1.358 Inches		
71-4450	AC Cod Rod Bearing-Tata Motors	2	STD,0.25,0.50,0.75,1.00	C/L	3.5404 Inches	3.6623 Inches	0.826 Inches	0.059 Inches	
55-4415/6	Cod Rod -Tata 352	6	SEMI, 0.010, 0.020	C/L	1.2616 Inches	1.4577 Inches	1.358 Inches		TATA TATA-OM 352 E/SE
55-4596/6	Cod Rod Bush-Tata Motors	6	SEMI, 0.010, 0.020	C/L	1.4173 Inches	1.5364 Inches	1.358 Inches		TATA TATA-OM 352 E/SE
H1210/5	Main Bearing-Tata	10	STD,0.25,0.50,0.75,1.00	C/L	3.4650 Inches	3.6623 Inches	0.949 Inches	0.097 Inches	
55-4420/4	Cod Rod Bush-Tata	4	SEMI, 0.010, 0.020	C/L	1.4173 Inches	1.5364 Inches	1.358 Inches		
H1218/7	Main Bearing-Tata	14	STD,0.25,0.50,0.75,1.00	C/L	2.8724 Inches	3.0716 Inches	1.253 Inches	0.098 Inches	
72-4410H	Main Bearing-Tata	2	0.250	C/L	2.8744 Inches	3.0716 Inches	1.256 Inches		
72-4456H	Main Bearing-Tata	1	STD, 0.50,0.75, 1.00, 1.25, 1.50	C/L	2.8744 Inches	3.0716 Inches	1.253 Inches		

Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
71-4397/6	Con Rod Bearing - Tata	12	STD,0.10,0.125,0.25,0.50,0.75,1.00,1.25,1.50	C/L	2.3628 Inches	2.5992 Inches	1.264 Inches	0.117 Inches	
71-4449	Cod Rod Bush-Tata Motors	2	STD,0.25,0.50,0.75,1.00	C/L	1.2585 Inches	1.3786 Inches	0.669 Inches	0.059 Inches	
55-4413/6	Cod Rod Bush-Tata Motors	6	SEMI, 0.010, 0.020	C/L	1.2598 Inches	1.4577 Inches	1.358 Inches		
55-4595/6	Cod Rod Bush-Tata Motors	6	SEMI, 0.010, 0.020	C/L	1.2598 Inches	1.3789 Inches	1.358 Inches		
N175/4	Cam Shaft Bush-Tata	4	SEMI, 0.060	C/L	2.2032 Inches	2.3634 Inches	1.035 Inches		
N176/5	Cam Shaft Bush-Tata	4	SEMI	C/L	2.2032 Inches	2.3634 Inches	1.035 Inches		
N185/4	Cam Shaft Bush-Tata	4	SEMI	C/L	2.2032 Inches	2.3634 Inches	1.035 Inches		
N185/3	Cam Shaft Bush-Tata	3	SEMI	C/L	2.2032 Inches	2.3634 Inches	1.035 Inches		
57-4440/12	Valve Rocker Bush-Tata	12	SEMI	C/L	0.7860 Inches	0.8682 Inches	0.906 Inches		
N186/4	Bushes-Tata	4	SEMI	C/L	2.1933 Inches	2.3634 Inches	1.029 Inches		
01-4397/6	Con Rod Bearing-Tata	12	STD,0.125,0.25,0.50,0.75,1.00	A/T	2.3628 Inches	2.5992 Inches	1.264 Inches	0.117 Inches	
H1202/7	Main Bearing-Tata	14	STD,0.25,0.50,0.75,1.00	A/T	2.8724 Inches	3.0716 Inches	0.949 Inches	0.098 Inches	TATA TATA-608 E/SE
H1203/7	Main Bearing -Tata	14	STD,0.25,0.50,0.75,1.00,1.25, 1.50	C/L	2.8724 Inches	3.0716 Inches	0.949 Inches	0.098 Inches	TATA TATA-608 E/SE
71-4397/6	Con Rod Bearing - Tata	12	STD, 0.10, 0.125, 0.25, 0.50,0.75, 1.00, 1.25, 1.50	C/L	2.3628 Inches	2.5992 Inches	1.264 Inches	0.117 Inches	TATA TATA-608 E/SE
A248/4	Thrust Washer -Tata	4	STD, 0.005, 0.009	C/L	3.2300 Inches	4.0980 Inches		0.127 Inches	TATA TATA-608 E/SE
55-4599	AC Cod Rod Bush-Tata	1	SEMI	C/L	0.6302 Inches	0.7488 Inches	0.868 Inches		TATA TATA-692 E/SE
H1257/7	Main Bearing-Tata	14	STD,0.25,0.50,0.75,1.00	C/L	2.8724 Inches	3.0716 Inches	0.949 Inches	0.098 Inches	TATA TATA-692 E/SE
H1255/7	Main Bearing-Tata	14	STD, 0.125, 0.25, 0.50,0.75, 1.00	C/L	2.8724 Inches	3.0716 Inches	0.949 Inches	0.098 Inches	TATA TATA-692 E/SE
A249/4	Thrust Washer-Tata	4	STD, 0.005, 0.009	C/L	3.2300 Inches	4.0980 Inches		0.127 Inches	TATA TATA-692 E/SE



Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
A247/4	Thrust Washer -Tata	4	STD, 0.005, 0.009	C/L	3.2300 Inches	4.0980 Inches		0.127 Inches	TATA TATA-692 E/SE
71-4397/6	Con Rod Bearing - Tata	12	STD,0.10,0.125,0.25,0.50,0.75,1.00,1.25,1.50	C/L	2.3628 Inches	2.5992 Inches	1.264 Inches	0.117 Inches	TATA TATA-692 E/SE
55-4412/6	Cod Rod Bush-Tata	6	SEMI, 0.010, 0.020	C/L	1.2598 Inches	1.3789 Inches	1.358 Inches		TATA TATA-608 E/SE
57-4604	Bearing Bush-Tata	1	SEMI	C/L	1.1810 Inches	1.4580 Inches	1.344 Inches		TATA TATA-692 E/SE
57-4605	Steering Gear Bush-Tata	1	SEMI	C/L	1.8236 Inches	1.9695 Inches	0.875 Inches		TATA TATA-692 E/SE
57-4606	Reverse Idler Gear Bush-Tata	1	SEMI	C/L	1.1878 Inches	1.3001 Inches	2.225 Inches		TATA TATA-692 E/SE
H1202/5	Main Bearing-Tata	10	STD,0.125,0.25,0.50,0.75,1.00	A/T	2.8724 Inches	3.0716 Inches	0.949 Inches	0.098 Inches	
H1203/5	Main Bearing -Tata	10	STD,0.10,0.125,0.25,0.50,0.75,1.00,1.25,1.50	C/L	2.8724 Inches	3.0716 Inches	0.949 Inches	0.098 Inches	
01-4400/4	Con Rod Bearing-Tata	8	STD,0.125,0.25,0.50,0.75,1.00	A/T	2.3628 Inches	2.5598 Inches	1.264 Inches	0.097 Inches	
55-4414/4	Cod Rod Bush-Tata	4	SEMI, 0.010, 0.020	C/L	1.4173 Inches	1.5364 Inches	1.358 Inches		
A248/4	Thrust Washer Bearing-Tata	4	STD, 0.005, 0.009	C/L	3.2300 Inches	4.0980 Inches		0.127 Inches	
H1206/5	Main Bearing -Tata	10	STD,0.125,0.25,0.50,0.75,1.00	A/T	3.4650 Inches	3.6623 Inches	0.949 Inches	0.097 Inches	
01-4400/4	Con Rod Bearing-Tata	8	STD,0.125,0.25,0.50,0.75,1.00	A/T	2.3628 Inches	2.5598 Inches	1.264 Inches	0.097 Inches	
H1207/5	Main Bearing -Tata	10	STD,0.10,0.125,0.25,0.50,0.75,1.00	C/L	3.4650 Inches	3.6623 Inches	0.949 Inches	0.097 Inches	
71-4400/4	Con Rod Bearing-Tata	8	STD,0.125,0.25,0.50,0.75,1.00	C/L	2.3628 Inches	2.5598 Inches	1.264 Inches	0.097 Inches	
55-4420/4	CR Bush-Tata	4	SEMI, 0.010, 0.020	C/L	1.4173 Inches	1.5364 Inches	1.358 Inches		



## Engine Bearing



Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
H1308/5	Main Bearing -Hyundai Santro 1.0/1.1L	10	STD,0.25,0.50,0.75,1.00	A/T	1.652 Inches	1.8118 Inches	0.634 Inches	0.079 Inches	
01-4857/4	Con Rod Bearing-Hyundai Santro 1.0/1.1L	8	STD,0.25,0.50,0.75,1.00	A/T	1.4946 Inches	1.6150 Inches	0.555 Inches	0.059 Inches	
H1260/4	Main Bearing-Maruti 800cc	8	STD,0.25,0.50,0.75,1.00	A/T	1.9685 Inches	2.1266 Inches	0.673 Inches	0.078 Inches	MARUTI MARUTI-800
A278/2	Thrust Washer-A278/2-Maruti 800cc	2	STD,0.25,0.50	A/T	2.874 Inches	2.2540 Inches		0.099 Inches	MARUTI MARUTI-800
01-4637/3	Con Rod Bearing-Maruti 800cc	6	STD,0.25,0.50,0.75,1.00	A/T	1.4943 Inches	1.6148 Inches	0.713 Inches	0.059 Inches	MARUTI MARUTI-800
55-4642/3	CR Bush(with Holes)-Maruti 800cc	3	STD	C/L	0.6299 Inches	0.7094 Inches	0.866 Inches		MARUTI MARUTI-800
55-4643/3	CR Bush (Prefin. with Holes)-Maruti 800cc	3	STD	C/L	0.6299 Inches	0.7099 Inches	0.866 Inches		MARUTI MARUTI-800
57-4645	Reverse Gear Bush-Maruti 800cc	3	STD	C/L	0.6299 Inches	0.7094 Inches	0.866 Inches		MARUTI MARUTI-800
H1301/4	Main Bearing -Maruti Alto	8	STD,0.25,0.50,0.75,1.00	A/T	1.7716 Inches	1.9298 Inches	0.673 Inches	0.078 Inches	
01-4837/3	Con Rod Bearing-Maruti Alto	6	STD,0.25,0.50,0.75,1.00	A/T	1.4943 Inches	1.6148 Inches	0.713 Inches	0.059 Inches	
55-4636/3	CR Bush-Maruti Alto	3	STD,0.25,0.50,0.75,1.00	C/L	0.6299 Inches	0.7094 Inches	0.866 Inches		MARUTI MARUTI-ALTO
H1261/5	Main Bearing -Maruti Gypsy/1000cc	10	STD,0.25,0.50,0.75,1.00	A/T	1.9685 Inches	2.1267 Inches	0.791 Inches	0.078 Inches	MARUTI MARUTI-GYPSY
01-4637/4	Con Rod Bearing-Maruti Gypsy/1000cc	8	STD,0.25,0.50,0.75,1.00	A/T	1.4943 Inches	1.6148 Inches	0.713 Inches	0.059 Inches	MARUTI MARUTI-1000 MARUTI MARUTI-GYPSY
55-4636/4	CR Bush (Without Holes)-Maruti Gypsy/1000cc	4	STD	C/L	0.6299 Inches	0.7094 Inches	0.866 Inches		MARUTI MARUTI-1000 MARUTI MARUTI-GYPSY
55-4642/4	CR Bush (With Holes)-Maruti Gypsy/1000cc	4	STD	C/L	0.6299 Inches	0.7094 Inches	0.866 Inches		MARUTI MARUTI-1000 MARUTI MARUTI-GYPSY
H1301/5	Main Bearing-Maruti Wagon R	10	STD,0.25,0.50,0.75,1.00	A/T	1.7716 Inches	1.9298 Inches	0.673 Inches	0.078 Inches	
01-4817/4	Con Rod Bearing-Maruti Wagon R	8	STD,0.25,0.50,0.75,1.00	A/T	1.4943 Inches	1.6149 Inches	0.713 Inches	0.059 Inches	

Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
01-4817/4	Con Rod Bearing-Maruti Wagon R	8	STD,0.25,0.50,0.75,1.00	A/T	1.4943 Inches	1.6149 Inches	0.713 Inches	0.059 Inches	
H1262/5	Main Bearing -Maruti Zen/YE2	10	STD,0.25,0.50,0.75,1.00	A/T	1.7696 Inches	1.9298 Inches	0.714 Inches	0.079 Inches	MARUTI MARUTI-ZEN
01-4640/4	Con Rod Bearing -Maruti Zen/YE2	8	STD,0.25,0.50,0.75,1.00	A/T	1.6119 Inches	1.7724 Inches	0.713 Inches	0.079 Inches	MARUTI MARUTI-ZEN
H1259/5	Main Bearing-Tata Indica	10	STD,0.25,0.50,0.75,1.00	A/T	1.9685 Inches	2.1189 Inches	0.673 Inches	0.074 Inches	TATA TATA-INDICA
71-4634/4	Con Rod Bearing-Tata indica	8	STD,0.25,0.50,0.75,1.00	C/L	1.7698 Inches	1.9162 Inches	0.777 Inches	0.072 Inches	
H1315/5	Main Bearing -GM Tavera 2.5L	10	STD,0.25,0.50,0.75,1.00	A/T	2.3584 Inches	2.5197 Inches	0.948 Inches	0.079 Inches	CHEVROLET CHEVROLET-TAVERA
01-4877/4	Con Rod Bearing -GM Tavera 2.5L	8	STD,0.25,0.50,0.75,1.00	A/T	2.0844 Inches	2.2047 Inches	1.010 Inches	0.059 Inches	CHEVROLET CHEVROLET-TAVERA
H1319/3	Main Bearing -Mahindra Maximo/Eagle	6	STD,0.25,0.50	A/T	2.2817 Inches	2.4415 Inches	0.807 Inches	0.078 Inches	MAHINDRA MAHINDRA MAXIMMO
71-4885/2	Con Rod Bearing -Mahindra Maximmo/Eagle	4	STD,0.25,0.50	C/L	1.8493 Inches	1.9692 Inches	0.827 Inches	0.059 Inches	MAHINDRA MAHINDRA MAXIMMO
H1318/5	Main Bearing -Mahindra 2.2L	10	STD,0.25,0.50,0.75	A/T	2.4388 Inches	2.5990 Inches	0.807 Inches	0.078 Inches	MAHINDRA MAHINDRA XYLO MAHINDRA MAHINDRA XUV 500
A325/4	Thrust Washer -Mahindra 2.2L	4	STD	A/T	2.9628 Inches	3.2205 Inches		0.096 Inches	MAHINDRA MAHINDRA XYLO MAHINDRA MAHINDRA XUV 500
01-4883/4	Con Rod Bearing -Mahindra /Eagle	8	STD,0.25,0.50,0.75	A/T	2.0067 Inches	2.1267 Inches	0.827 Inches	0.059 Inches	MAHINDRA MAHINDRA XYLO MAHINDRA MAHINDRA XUV 500
55-4982/4	CR Bush-Mahindra 2.2L	4	SEMI	C/L	1.2237 Inches	1.3394 Inches	1.094 Inches		MAHINDRA MAHINDRA XYLO MAHINDRA MAHINDRA XUV 500
H1317/5	Main Bearing -Mahindra Scorpio 2.5	10	STD,0.25,0.50,0.75	A/T	2.1246 Inches	2.2975 Inches	1.072 Inches	0.085 Inches	MAHINDRA MAHINDRA SCORPIO MAHINDRA MAHINDRA XYLO
A317/4	Thrust Washer -Mahindra Scorpia 2.5	4	STD	A/T	2.4500 Inches	3.1496 Inches		0.092 Inches	MAHINDRA MAHINDRA XYLO MAHINDRA MAHINDRA SCORPIO



Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
01-4881/4	Con Rod Bearing -Mahindra	8	STD,0.25,0.50,0.75	A/T	2.1247 Inches	2.2970 Inches	1.044 Inches	0.085 Inches	MAHINDRA MAHINDRA SCORPIO MAHINDRA MAHINDRA XYLO
55-4950/4	Con Rod bush-Mahindra	4	STD	C/L	1.1878 Inches	1.3002 Inches	1.287 Inches		MAHINDRA MAHINDRA SCORPIO MAHINDRA MAHINDRA XYLO
H1316/5	Main Bearing -Tata Safari	10	STD,0.25,0.50,0.75	A/T	2.3608 Inches	2.5094 Inches	1.181 Inches	0.073 Inches	TATA TATA-SAFARI
01-4879/4	Con Rod Bearing -Tata Safari	8	STD,0.25,0.50,0.75	A/T	1.9672 Inches	2.1145 Inches	1.142 Inches	0.072 Inches	TATA TATA-SAFARI
55-4953/4	Con Rod Bush-Tata Safari	4	STD	C/L	1.2238 Inches	1.3396 Inches	1.000 Inches		TATA TATA-SAFARI
H1256/5	Main Bearing -Tata Sumo	10	STD,0.25,0.50,0.75,1.00	C/L	2.3608 Inches	2.5094 Inches	1.181 Inches	0.073 Inches	TATA TATA-SUMO
71-4603/4	Con Rod Bearing -Tata Sumo	8	STD,0.25,0.50,0.75,1.00	C/L	1.9672 Inches	2.1145 Inches	1.142 Inches	0.072 Inches	TATA TATA-SUMO
55-4610/4	Con Rod Bush-Tata Sumo	4	SEMI, 0.010	C/L	0.9761 Inches	1.0640 Inches	0.955 Inches		TATA TATA-SUMO
H1259/3	Main Bearing-Tata Ace/107	6	STD,0.25,0.50,0.75,1.00	A/T	1.9685 Inches	2.1189 Inches	0.673 Inches	0.074 Inches	TATA TATA-ACE
71-4634/2	Con Rod Bearing-Tata Ace	4	STD,0.25,0.50,0.75,1.00	C/L	1.7701 Inches	1.9162 Inches	0.777 Inches	0.072 Inches	TATA TATA-ACE
71-4634/2	Con Rod Bearing-Tata Ace	4	STD,0.25,0.50,0.75,1.00	C/L	1.7701 Inches	1.9162 Inches	0.777 Inches	0.072	TATA TATA-ACE
A277/4	Thrust Washer -Tata Sumo	4	STD, 0.001, 0.002, 0.003	C/L	3.0277 Inches	3.2910 Inches		0.100 Inches	TATA TATA-SUMO
01-4817/3	Con Rod Bearing Maruti Alto	6	STD,0.25,0.50,0.75,1.00	A/T	1.4943 Inches	1.6148 Inches	0.713 Inches	0.059 Inches	



## Engine Bearing



Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
H1270/4	"F/Main Bearing(U+L)/I/ Main Bearing (U+L)R/Main Bearing"	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7490inches	2.9170inches	1.274 inches, 0.937 inches, 1.542inches	0.083inches	SIMPSON PERKINS SIMPSON PERKINS 3,CYL
A281/4	THRUST WASHER	4	STD, 0.003, 0.005, 0.010, 0.015, 0.020, 0.025	C/L	3.0550 inches	3.5620 inches		0.120 inches	SIMPSON PERKINS SIMPSON PERKINS 3,CYL
71-4691/3	Con Rod Bearing	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.2490 inches	2.3955 inches	1.190 inches	0.072 inches	SIMPSON PERKINS SIMPSON PERKINS 3,CYL
55- 4916/3	CR Bush	3	SEMI, 0.010. 0.020	C/L	1.2500 INCHES	1.3763 INCHES	1.057 INCHES		SIMPSON PERKINS SIMPSON PERKINS 3,CYL
57- 4687/4	Spindle Bush With Tin Flash	4	SEMI	C/L	1.2500 INCHES	1.3763 INCHES	1.057 INCHES		SIMPSON PERKINS SIMPSON PERKINS 3,CYL
H1270/5	F/ Main Bearing	10	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7490inches	2.9170inches	1.274 inches	0.083inches	SIMPSON PERKINS SIMPSON PERKINS 4CYL
H1270/5	"I/ Main Bearing", "R/Main Bearing"	10	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7490inches	2.9170inches	0.937 inches/ 1.542 inches	0.083inches	SIMPSON PERKINS SIMPSON PERKINS 4CYL
71-4691/4	Con Rod Bearing	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.2490 inches	2.3955 inches	1.190 inches	0.072 inches	SIMPSON PERKINS SIMPSON PERKINS 4CYL
71-4647	Con Rod Bearing	2	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.9589 inches	3.1109 inches	1.331 inches	0.074 inches	EICHER TRACTOR 115
55-4648	CR Bush	1	SEMI, 0.010. 0.020	C/L	1.6812 inches	1.8156 inches	1.675 inches		EICHER TRACTOR 115
H1284/3	F/C/R Main Bearing	6	STD, 0.25, 0.50,	A/T	3.3532 inches	3.5858 inches	1.575 inches	0.115 inches	ESCORTS E-335 S-312-C
H1263/3	F/C/R Main Bearing	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	3.1563 inches	3.3868 inches	1.575 inches	0.114inches	ESCORTS E-335 S-312-C
A282/4	THRUST WASHER	4	STD, 0.020, 0.040	C/L	3.3960 inches	4.1340 inches		0.134 inches	ESCORTS E-335 S-312-C
71-4652/2	Con Rod Bearing	4	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.9489 inches	3.1108 inches	1.339 inches	0.079 inches	ESCORTS E-335 S-312-C
71-4830/2	Con Rod Bearing New Type	4	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.9489 inches	3.1108 inches	1.339 inches	0.079 inches	ESCORTS E-335 /E-345
55-4653/2	CR Bush	2	SEMI, 0.010. 0.020	C/L	1.4960 inches	1.6551 inches	1.482 inches		ESCORTS E-335 S-312-C
H1264/3	F/C/R Main Bearing	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	3.3532 inches	3.5858 inches	1.575 inches	0.115 inches	ESCORTS E-335 /E-345
A279/4	THRUST WASHER	4	STD	C/L	3.5920 inches	4.3310 inches		0.141 inches	ESCORTS E-335 /E-345
55-4657/2	CR Bush	2	SEMI, 0.010. 0.020	C/L	1.6535 inches	1.8125 inches	1.640 inches		ESCORTS E-335 /E-345
H 1264/4	Main Bearing	8	STD, 0.25, 0.50,	C/L	3.3532 inches	3.5858 inches	1.575 inches	0.115 inches	ESCORTS E-355 /340, 3CYL

Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
71-4711/3	Con Rod Bearing	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.5973 inches	2.7564 inches	1.260 inches	0.078 inches	ESCORTS E-355 /340, 3CYL
H1284/4	mai	8	STD, 0.25, 0.50,	A/T	3.3532 inches	3.5858 inches	1.575 inches	0.115 inches	ESCORTS E-355 /340, 3CYL
H 1284/4	Main Bearing	8	STD, 0.25, 0.50,	A/T	3.3532 inches	3.5858 inches	1.575 inches	0.115 inches	ESCORTS E-355 /340, 3CYL
H 1265/4	Main Bearing	8	STD, 0.25, 0.50, 0.75, 1.00	A/T	2.2835 inches	2.4811 inches	0.984 inches	0.098 inches	ESCORTS E- 430/435
71-4659/3	Con Rod Bearing	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.0468 inches	2.2052 inches	1.083 inches	0.078 inches	ESCORTS E- 430/435
H 1335/4	"Main Bearing Flange Bearing"	8	STD, 0.25, 0.50,	C/L	3.3722 inches	3.6250 inches	1.000 inches	0,125 inches	ESCORTS AVL, FT-70
71-4964/3	Con Rod Bearing Escorts Tractor	6	STD, 0.25, 0.50,	C/L	2.7492 inches	2.9063 inches	1.196 inches	0,077 inches	ESCORTS AVL, FT-70
H 1335/	Main Bearing Flange BearingFord Tractor	8	STD, 0.25, 0.50,	C/L	3.3722 inches	3.6250 inches	1.000 inches	0.125 inches	FORD FORD
57-4714/2	Brake Padel Shaft Bush Ford	2	STD	C/L	1.1574 inches	1.2500 inches	1.010 inches		FORD FORD
H 1266/4	F/I/R Main Bearing-Ford Farm Tract	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	3.3722 inches	3.6250 inches	1.110 inches	0.125 inches	FORD FARM TRACT 50,55,60
H 1286/4	F/I/R Main Bearing-Ford Farm Tract	8	STD, 0.25, 0.50, 0.75, 1.00	A/T	3.3722 inches	3.6250 inches	1.110 inches	0.125 inches	FORD FARM TRACT 50,55,60
71-4662/3	Con Rod Bearing Ford	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7485 inches	2.9420 inches	1.410 inches	0.095 inches	FORD FARM TRACT 50,55,60
01-4662/3	Con Rod Bearing Ford	6	STD, 0.25, 0.50, 0.75, 1.00	A/T	2.7485 inches	2.9420 inches	1.410 inches	0.095 inches	FORD FARM TRACT 50,55,60
55- 4663/3	CR Bush Ford	3	SEMI, 0.010. 0.020	C/L	1.5000 inches	1.6260 inches	1.620 inches		FORD FARM TRACT 50,55,60
N 190/4	Cam Shaft Bush Ford	4	SEMI	C/L	2.3930 inches	2.5355 inches	0.770 iches		FORD FARM TRACT 50,55,60
57- 4705/4	Front Wheel Spindle Bush- Ford	4	STD	C/L	1.2713 inches	1.4675 inches	1.500 inches		FORD FARM TRACT 50,55,60
57- 4699/10	Spindle Bush Swaraj	10	SEMI	C/L	1.4032 inches	1.5323 inches	1.336 inches		SWARAJ TRACTORS 735 FE
57- 4699/4	Spindle Bush Swaraj	4	SEMI	C/L	1.4032 inches	1.5323 inches	1.336 inches		SWARAJ TRACTORS 735 FE
57- 4699/2	Spindle Bush Swaraj	2	SEMI	c	1.4032 inches	1.5323 inches	1.336 inches		SWARAJ TRACTORS 735 FE
H 1267/3	"F/C/M Main Bearing R/Main Bearing Zetor	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7559 inches	2.9929 inches	1.260-1.417 inches	0.117 inches	HMT ZETOR-2011/2511/2045
A 280/4	THRUST WASHER Zetor	4	STD, RS1, RS2, RS3, RS4	C/L	3.1300 inches	3.9370 inches		0.121 inches	HMT ZETOR-2011/2511/2045
71-4668/2	Con Rod Bearing Zetor	4	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.3622 inches	2.5204 inches	1.260 inches	0.078 inches	HMT ZETOR-2011/2511/2045
55-4673/2	CR Bush Zetor	2	SEMI, 0.010. 0.020	C/L	1.3780 inches	1.5758 inches	1.378 inches		HMT ZETOR-2011/2511/2045

Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
H 1267/4	F/C/R Main Bearing Zetor	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7559 inches	2.9929 inches	1.260-1.417 inches	0.117 inches	HMT HMT ZETOR-3011/3511/3045
71-4668/3	Con Rod Bearing Zetor	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.3622 inches	2.5204 inches	1.260 inches	0.078 inches	HMT HMT ZETOR-3011/3511/3045
H 1267/5	F/C/R Main Bearing Zetor	10	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7559 inches	2.9929 inches	1.260-1.417 inches	0.117 inches	HMT ZETOR -5911
71-4668/4	Con Rod Bearing Zetor	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.3622 inches	2.5204 inches	1.260 inches	0.078 inches	HMT ZETOR -5911
H 1274/3	F/C/R Main Bearing Zetor	6	STD, 0.25, 0.50,	C/L	2.7559 inches	2.9929 inches	1.260-1.417 inches	0.117 inches	HMT AVL 2CYL
H 1309/4	F/C/R Main Bearing New type, Kirloskar	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7547 inches	2.9338 inches	1.068 inches	0.088 inches	KIRLOSKAR TRACTOR KIRLOSKAR RA 3
H 1271/4	F/C/R Main Bearing , Kirloskar	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7524 inches	2.9535 inches	1.185 inches	0.099 inches	KIRLOSKAR TRACTOR KIRLOSKAR RA 3
71-4695/3	Con Rod Bearing Kirloskar	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.0935 inches	2.2935 inches	1.185 inches	0.099 inches	KIRLOSKAR TRACTOR KIRLOSKAR RA 3
55-4698/3	CR Bush kirloskar	6	SEMI, 0.010. 0.020	C/L	1.3780 inches	1.5223 inches	1.545 inches		KIRLOSKAR TRACTOR KIRLOSKAR RA 3
H 1302/4	Main Bearing Kirloskar HA3/1040 4R Old / New Type	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7547 inches	2.9338 inches	1.068 inches	0.088 inches	KIRLOSKAR TRACTOR KIRLOSKAR HA3/1040 4R KIRLOSKAR TRACTOR HA3/1040 4R NEW TYPE
71-4829/3	Con Rod Bearing Kirloskar HA3/1040 4R	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.3604 inches	2.5210 inches	0.984 inches	0.079 inches	KIRLOSKAR TRACTOR KIRLOSKAR
H 1302/2	Main Bearing Kirloskar HA3/1040 4R	4	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.7547 inches	2.9338 inches	1.068 inches	0.088 inches	KIRLOSKAR TRACTOR KIRLOSKAR HA3/1040 4R
71- 4829/1	Con Rod Bearing Kirloskar HA3/1040 4R	2	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.3604 inches	2.5210 inches	0.984 inches	0.079 inches	KIRLOSKAR TRACTOR KIRLOSKAR HA3/1040 4R
71-4985/3	Con Rod Bearing Kirloskar HA3/1040 4R New Type	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.3622 inches	2.5210 inches	0.984 inches	0.079 inches	KIRLOSKAR TRACTOR HA3/1040 4R NEW TYPE
H 1268/5	F/C/I/R Main Bearing Mahindra B275	10	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.1257 inches	2.2975 inches	1.072- 1.318 inches	0.085 inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA B275
71-4674/4	Con Rod Bearing Mahindra B275	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	0.7505 inches	0.8760 inches	1.074 inches	0.062 inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA B275

Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
55-4677/4	CR Bush Mahindra B275	4	SEMI, 0.010. 0.020	C/L	1.1031 inches	1.1590 inches	1.223 inches		MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA B275
57-4677/4	Steering Knuckle Pivot Pin Bush Mahindra B275	4	STD	C/L	1.3599 inches	1.4850 inches	2.885 inches		MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA B275
57-4679/2	Front Axle Pivot Pin Sleeve Bush Mahindra B275	2	STD	C/L	1.1200 inches	1.3760 inches	2.260 inches		MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA B275
H 1269/3	Main Bearing Flange Bearing Mahindra AVL 2 CYL	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.1257 inches	2.2975 inches	1.072- 1.318 inches	0.085 inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL 2CYL
71-4674/2	Con Rod Bearing Mahindra AVL 2CYL	4	STD, 0.25, 0.50, 0.75, 1.00	C/L	0.7505 inches	0.8760 inches	1.074 inches	0.062 inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL 2CYL
H 1269/4	Main Bearing Flange Bearing Mahindra AVL 3 CYL	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.1257 inches	2.2975 inches	1.072- 1.318 inches	0.085 inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL 3CYL
71-4674/3	Con Rod Bearing Mahindra AVL 3CYL	6	STD, 0.25, 0.50, 0.75, 1.00	C/L	0.7505 inches	0.8760 inches	1.074 inches	0.062 inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL 3CYL
H 1269/5	F/C/R Main Bearing Main Bearing Mahindra AVL 4CYL	10	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.1257 inches	2.2975 inches	1.072- 1.318 inches	0.085 inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL 4CYL
55-4683/4	CR Bush Mahindra AVL 4CYL	4	SEMI, 0.010. 0.020	C/L	1.1023 inches	1.2195 inches	0.984 inches		MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL 4CYL
N 191/3	Cam Bush(F/C/R) MDI 3000/3200 Mahindra AVL	3	SEMI	C/L	1.8120 inches	1.9735 inches	1.103 inches		MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL
H 1273/5	Main Bearing Mahindra AVL	10	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.1257 inches	2.2975 inches	1.072 inches	0.085 inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL
71-4682/4	Con Rod Bearing Mahindra AVL	8	STD, 0.25, 0.50, 0.75, 1.00	C/L	2.1257 inches	2.2975 inches	1.044 inches	0.085 inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL
H1272/5	Main Bearing Eicher Mitsubishi	10	STD, 0.25, 0.50	C/L	3.0677 Inches	3.2292 Inches	1.068 Inches	0.079 Inches	EICHER TRACTOR MITSUBISHI
A283/2	Thrust Washer Eicher Mitsubishi	2	STD, 0.15, 0.30, 0.45	C/L	3.5920 Inches	4.3300 Inches		0.129 Inches	EICHER TRACTOR MITSUBISHI
71-4697/4	Con Rod Bearing Eicher Mitsubishi	8	STD, 0.25, 0.50	C/L	2.3595 Inches	2.5205 Inches	1.304 Inches	0.079 Inches	EICHER TRACTOR MITSUBISHI



Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
55-4703/4	CR Bush Eicher Mitsubishi	4	SEMI	C/L	1.2616 Inches	1.4576 Inches	1.319 Inches		EICHER TRACTOR MITSUBISHI
H1264/4	Main Bearing ESCORTS 355/340, 3 Cyl	8	STD, 0.25, 0.50	C/L	3.3532 Inches	3.5858 Inches	1.575 Inches	0.115 Inches	ESCORTS E-355 /340, 3CYL
H1265/4	Main Bearing ESCORTS E 430/435	8	STD,0.25,0.50,0.75,1.00	A/T	2.2835 Inches	2.4811 Inches	0.984 Inches	0.098 Inches	ESCORTS E- 430/435
H1335/4	Main Bearing ESCORTS AVL, FT-70	8	STD, 0.25, 0.50	C/L	3.3722 Inches	3.6250 Inches	1.000 Inches	0.125 Inches	ESCORTS AVL, FT-70
H1266/4	F/I/R Main Bearing FORD FARM TRACT 50,55,60	8	STD,0.25,0.50,0.75,1.00	C/L	3.3722 Inches	3.6250 Inches	1.110 Inches	0.125 Inches	FORD FARM TRACT 50,55,60
H1286/4	F/I/R Main Bearing FORD FARM TRACT 50,55,60	8	STD,0.25,0.50,0.75,1.00	A/T	3.3722 Inches	3.6250 Inches	1.110 Inches	0.125 Inches	FORD FARM TRACT 50,55,60
55-4663/3	CR Bush FORD FARM TRACT 50,55,60	3	SEMI, 0.010, 0.020	C/L	1.5000 Inches	1.6260 Inches	1.620 Inches		FORD FARM TRACT 50,55,60
N190/4	Cam Shaft Bush FORD FARM TRACT 50,55,60	4	SEMI	C/L	2.3930 Inches	2.5355 Inches	0.770 Inches		FORD FARM TRACT 50,55,60
57-4705/4	Front Wheel Spindle Bush FORD FARM TRACT 50,55,60	4	STD	C/L	1.2713 Inches	1.4675 Inches	1.500 Inches		FORD FARM TRACT 50,55,60
H1267/3	F/C/Main Bearing HMT ZETOR - 2011/2511/2045	6	STD,0.25,0.50,0.75,1.00	C/L	2.7559 Inches	2.9929 Inches		0.117 Inches	HMT ZETOR-2011/2511/2045
A280/4	Thrust Washer HMT ZETOR - 2011/2511/2045	4	STD, RS1, RS2, RS3, RS4	C/L	3.1300 Inches	3.9370 Inches		0.121 Inches	HMT ZETOR-2011/2511/2045
H1267/4	F/C/Main Bearing Zetor	8	STD,0.25,0.50,0.75,1.00	C/L	2.7559 Inches	2.9929 Inches	"1.260 1.417" Inches	0.117 Inches	HMT HMT ZETOR-3011/3511/3045
H1267/5	F/C/Main Bearing Zetor	10	STD,0.25,0.50,0.75,1.00	C/L	2.7559 Inches	2.9929 Inches		0.117 Inches	HMT ZETOR -5911
H1274/3	F/C/Main Bearing HMT AVL 2 Cyl	6	STD, 0.25, 0.50	C/L	2.7559 Inches	2.9929 Inches	"1.260 1.417" Inches	0.117 Inches	HMT AVL 2CYL
H1309/4	F/C/Main Bearing KIRLOSKAR	8	STD,0.25,0.50,0.75,1.00	C/L	2.7547 Inches	2.9338 Inches	1.068 Inches	0.088 Inches	KIRLOSKAR TRACTOR KIRLOSKAR RA 3
H1271/4	F/C/Main Bearing KIRLOSKAR	8	STD,0.25,0.50,0.75,1.00	C/L	2.7524 Inches	2.9535 Inches	1.185 Inches	0.099 Inches	KIRLOSKAR TRACTOR KIRLOSKAR RA 3

Part Number	Name	Components Per Set	Size Available	Material	Shaft Diameter	Bore Diameter	Length	Wall Thickness	Application
H1302/4	Main Bearing KIRLOSKAR	8	STD,0.25,0.50,0.75,1.00	C/L	2.7547 Inches	2.9338 Inches	1.068 Inches	0.088 Inches	KIRLOSKAR TRACTOR KIRLOSKAR
H1302/2	Main Bearing KIRLOSKAR	4	STD,0.25,0.50,0.75,1.00	C/L	2.7547 Inches	2.9338 Inches	1.068 Inches	0.088 Inches	KIRLOSKAR TRACTOR KIRLOSKAR
71-4829/1	Con Rod Bearing KIRLOSKAR	2	STD,0.25,0.50,0.75,1.00	C/L	2.3604 Inches	2.5210 Inches	0.984 Inches	0.079 Inches	KIRLOSKAR TRACTOR KIRLOSKAR
H1268/5	F/C/I Main Bearing MAHINDRA	10	STD,0.25,0.50,0.75,1.00	C/L	2.1257 Inches	2.2975 Inches		0.085 Inches	MAHINDRA B-275
57-4678/4	Steering Knuckle Pivot Pin Bush MAHINDRA	4	STD	C/L	1.3599 Inches	1.4850 Inches	2.885 Inches		MAHINDRA B-275
H1269/3	Main Bearing MAHINDRA AVL	6	STD,0.25,0.50,0.75,1.00	C/L	2.1257 Inches	2.2975 Inches		0.085 Inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL 2CYL
H1269/4	Main Bearing MAHINDRA	8	STD,0.25,0.50,0.75,1.00	C/L	2.1257 Inches	2.2975 Inches		0.085 Inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL 3CYL
H1269/5	F/C/Main Bearing MAHINDRA AVL	10	STD,0.25,0.50,0.75,1.00	C/L	2.1257 Inches	2.2975 Inches		0.085 Inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL 4CYL
N191/3	Cam Bush (F/C/R) MAHINDRA AVL	3	SEMI	C/L	1.8120 Inches	1.9735 Inches	1.103 Inches		MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL
H1273/5	Main Bearing MDI	10	STD,0.25,0.50,0.75,1.00	C/L	2.1257 Inches	2.2975 Inches	1.072 Inches	0.085 Inches	MAHINDRA GUJARAT TRACTOR LIMITED MAHINDRA AVL
57-4699/10	Spindle Bush SWARAJ TRACTOR	10	SEMI	C/L	1.4032 Inches	1.5323 Inches	1.336 Inches		SWARAJ TRACTORS 735 FE
57-4699/4	Spindle Bush SWARAJ TRACTOR	4	SEMI	C/L	1.4032 Inches	1.5323 Inches	1.336 Inches		SWARAJ TRACTORS 735 FE
57-4699/2	Spindle Bush SWARAJ TRACTOR	2	SEMI	C/L	1.4032 Inches	1.5323 Inches	1.336 Inches		SWARAJ TRACTORS 735 FE
55-4916/3	CR Bush SIMPSON PERKINS	3	SEMI, 0.010, 0.020	C/L	1.2500 Inches	1.3762 Inches	1.057 Inches		SIMPSON PERKINS SIMPSON PERKINS 3,CYL
57-4687/4	Spindle Bush With tin flash SIMPSON PERKINS	4	SEMI	C/L	1.2500 Inches	1.3762 Inches	1.057 Inches		SIMPSON PERKINS SIMPSON PERKINS 3,CYL